TECHNICAL DATA

提出書類管理 No. 37,606

ロックナット16-22用 ステンレス鋼 材質証明書

鋼 材 検 査 証 明 書
INSPECTION CERTIFICATE

Nippon Steel Corporation

SHIPPER: MARUBENI
REFERENCE No.: 8573 -L0HY0504
CONTRACT No.:
COMMODITY: HOT-ROLLED STAINLESS STEEL SHEETS IN COIL
SPECIFICATION: JIS G4304 SUS304
NOTE: HEAT TREATMENT:SOLUTION HEAT TREATMENT 1080C SOSED WATER COOLED

CUSTOMER: HANWA KOZAI
CUSTOMER'S CONTROL No.:

CERTIFICATE No.: PAGE 1/1
DATE OF ISSUE:

SIZE mm	QUANTITY	MASS KG	CAST NO.	INSPECTION No. COIL NO.	TENSILE TEST 0.2% YS N/MM2	TS	EL %	BEND TEST	IMPACT TEST AVE	EACH	HV	C	Si	Mn	P	S	Ni	CR	Mo	Cu
				SPEC MIN	205	520	40				200						8.00	18.00		
				MAX								0.08	1.00	2.00	0.045	0.030	10.50	20.00		
4.0X1524XC 06																				
		11,019	E79753	01-21754-53-9878 A	271	628	57				160	0.05	0.48	0.86	0.027	0.002	8.18	18.13		
TOTAL		11,019																		

NOTES: GL: Gauge Length, A: 50mm C: 70mm E: 80mm G: 200mm H: JIS 25A/B, P: YS: Yield Point, RA: Reduction of Area, a: Acceptable, Rockwell B Scale, HBC: Hardness C Scale, HV: Vickers, HBS: Brinell, ACS: Acceptable Grain Size No., PWT: Powdered Weight Test, CF: Cyanide Free Process, LE: Lateral Expansion, P: Pocket Analysis

上記注文品は、特約書の規格または仕様に従って製造され、その要求事項を満足していることを証明します。

K. Ohmara
MANAGER, INSPECTION
HIKARI WORKS

'098 J 03- 34

製造元： 新日本製鐵
規 格： JIS G 4305 SUS(304)
寸 法 ： 4.0×1524×XC

管理フイルム No. G010-20021211-L123

株式会社ジョイント工業
品質保証課